

SWITCH Push Buttons

KNX Modular Switches

KNX Modular Push Button Multi
Color 1 Gang 2M



KNX Modular Push Button Multi
Color 2 Gang 2M



KNX Modular Push Button Multi
Color 3 Gang 3M



■ MAIN FEATURES

- Elevate your automation experience with our diverse range of KNX push buttons, available in 1 gang, 2 gang, and 3 gang configurations, allowing you to customize your control to fit seamlessly into your lifestyle.
- Change the ambiance of your place with each key featuring two multi-color LEDs.
- Control your KNX system with the push buttons, empowering you to effortlessly command actuators, dim, turn on and off lights, move blinds up and down, and even save and recall your favorite light scenes.
- Unlock the full potential by using push buttons to send temperature, priority, percentage, and HVAC operation mode values.
- Enjoy the convenience of saving scene functions with a simple 3-4 second press, making your place truly responsive to your needs.

- Personalize your experience with customizable behaviors through both short and long key depressions.
- Introducing the advanced WRKT64215NC, WRKT64225NC, and WRKT64335NC models, equipped with on-board temperature and humidity sensors—taking smart home control to a whole new level. Elevate your environment with precision and style.
- Can be located into all frames of Thea Modular Series; Optima, Sistema and Ultima.

■ FUNCTIONS

- Switching Control
- Dimming Control
- Blinds Control
- Value Dimming Control
- Value Transmitter Control

■ TECHNICAL DATA


Programming Mode	S Mode
Power Supply	21 to 32 V DC via KNX Bus
Current Draw From Bus Voltage	Max 10 mA
Bus Connection	Bus Terminal
Type of Protection	IP 20 to EN 60529
Degree of Pollution	2 to IEC 6066-1
Protection Class	Class III to IEC 61140
Overvoltage Class	Class III to IEC 60664-1
Temperature Range	Operation -5 °C...+45 °C Storage -10 °C...+55 °C Transport -25 °C...+70 °C
Relative Humidity	0% to 100%
Relative Humidity Measurements (for models with sensors)	-0 °C...+45 °C
Cable Type	Twisted Pair

■ PRODUCT CODES




PRODUCT	PRODUCT CODES
KNX Modular Push Button Multi Color 1 Gang 2M	WRKT63215NC
KNX Modular Push Button Multi Color 2 Gang 2M	WRKT63225NC
KNX Modular Push Button Multi Color 3 Gang 3M	WRKT63335NC
KNX Modular Push Button Multi Color+Temp 1 Gang 2M	WRKT64215NC
KNX Modular Push Button Multi Color+Temp 2 Gang 2M	WRKT64225NC
KNX Modular Push Button Multi Color+Temp 3 Gang 3M	WRKT64335NC

■ DIMENSIONS

1 GANG (2M) / 2 GANG (2M)



3 GANG (3M)



SWITCH Push Buttons

KNX Modular Switches

KNX Modular Push Button Multi
Color 4 Gang 2M



KNX Modular Push Button Multi
Color 4 Gang 4M



■ MAIN FEATURES

- Elevate your automation experience with our cutting-edge KNX push buttons, now available in sleek 4-gang configurations.
- Change the ambiance of your place with each key featuring two multi-color LEDs.
- Control your KNX system with the push buttons, empowering you to effortlessly command actuators, dim, turn on and off lights, move blinds up and down, and even save and recall your favorite light scenes.
- Unlock the full potential by using push buttons to send temperature, priority, percentage, and HVAC operation mode values.

- Enjoy the convenience of saving scene functions with a simple 3-4 second press, making your place truly responsive to your needs
- Personalize your experience with customizable behaviors through both short and long key depressions.
- Introducing the advanced WRKT64245NC and WRKT64445NC models, equipped with on-board temperature and humidity sensors—taking smart home control to a whole new level. Elevate your environment with precision and style.

■ FUNCTIONS

- Switching Control
- Dimming Control
- Blinds Control
- Value Dimming Control
- Value Transmitter Control

■ TECHNICAL DATA



Programming Mode	S Mode
Power Supply	21 to 32 V DC via KNX Bus
Current Draw From Bus Voltage	Max 10 mA
Bus Connection	Bus Terminal
Type of Protection	IP 20 to EN 60529
Degree of Pollution	2 to IEC 6066-1
Protection Class	Class III to IEC 61140
Overvoltage Class	Class III to IEC 60664-1
Temperature Range	Operation -5 °C...+45 °C Storage -10 °C...+55 °C Transport -25 °C...+70 °C
Relative Humidity	0% to 100%
Relative Humidity Measurements (for models with sensors)	-0 °C...+45 °C
Cable Type	Twisted Pair

■ PRODUCT CODES

PRODUCT	PRODUCT CODES
KNX Modular Push Button Multi Color 4 Gang 2M	WRKT63245NC
KNX Modular Push Button Multi Color 4 Gang 4M	WRKT63445NC
KNX Modular Push Button Multi Color+Temp 4 Gang 2M	WRKT64245NC
KNX Modular Push Button Multi Color+Temp 4 Gang 4M	WRKT64445NC

■ DIMENSIONS

4 GANG (2M)



4 GANG (4M)

